



1. Product description

KEIM Lignosil-Verano is a silicate greying glaze for non-dimensionally stable and limited dimensionally stable wooden building components outside. It simulates a greyed, patinated surface like it occurs on natural wood after years of weathering. KEIM Lignosil-Verano is subject to a natural ageing process and equalizes in this way the visual differences which can appear by uneven weathering of exposed and protected surfaces of uncoated wood.

Please note: KEIM Lignosil-Verano is neither a wood protective agent according to DIN 68800 nor a coating as per DIN EN 927.

2. Field of application

Silicate greying glaze as part of the KEIM Lignosil-System for the design of non-dimensionally stable and limited dimensionally stable wood components outside, preferably used on saw-rough surfaces.

3. Product properties

- Simulates a natural, greyed, patinated wood surface
- Biocide-free
- Colour-stable, lightfast
- Matt, natural appearance
- Good adhesion
- Non-film forming
- Open to diffusion
- Particularly economical

Material characteristics

- Specific weight: approx. 1.1 – 1.2 g/cm³
- Diffusion-equivalent air layer thickness:
 $s_d^* < 0.02$ m (DIN EN ISO 12572 Wet-Cup)
- No water protection acc. to DIN EN 927-2

Colour shades

On request

4. Application instructions

Substrate preparation

The substrate must be sound, dry (wood moisture content below 18% acc. to technical information No. 18 by BFS), clean, free of dust, loose parts and any other substances with separative properties such as oil.

Application

KEIM Lignosil-Verano can be applied in one or two coats depending on the desired appearance. Application can be performed by paint brush, roller, airless sprayer or by industrial coating procedures. Mechanical defects must be repaired with original material.

Note: The colour effect of KEIM Lignosil-Verano depends on the wood type, substrate quality as well as the way of application. It can be only determined by trial areas applied to the structure. When using aqueous wood coatings, discolourations due to staining wood ingredients may occur.

Application conditions

Ambient and substrate temperature $> +5^\circ\text{C}$. Apply in dry weather only. Do not apply in strong sunlight, onto sun-heated substrates or in strong wind. Protect coated surfaces from too fast drying, direct sunlight, wind and rain also after application.

Consumption

For one coat approx. 0.1 - 0.2 l/m² of KEIM Lignosil-Verano.

This consumption value is a guide value. Exact values depend on substrate texture and application method and can only be determined by trial areas.

Drying time

Approx. 6 hours at 23°C and 50% relative atmospheric humidity. Lower temperatures and/or higher relative humidity extend the drying.

Cleaning of tools

With water. During breaks tools should be kept in the glaze material or in water.

5. Packaging

5 l and 20 l container

6. Storage

Shelf life is approx. 12 months in sealed container under cool, frost-free conditions. Protect from heat and direct sun.

7. Disposal

EC Waste Code No. 08 11 02



Any residues must be emptied out of containers before recycling.

Note: Wood treated with KEIM Lignosil falls under class A II according to the waste wood ordinance (laminated, coated, lacquered waste wood without halogen-organic compounds in the coating and without wood preservatives).

8. Safety instructions

GISBAU Product Code/GISCODE: M-SK 01

Provide appropriate protection for surfaces which are not to be coated (e.g. glass, natural stone, ceramics etc.). Any splashes on surrounding surfaces or traffic areas must be rinsed off immediately with plenty of water. Protect the eyes and skin from splashes. Keep out of reach of children.

Please refer to the EC Safety Data Sheets

The stated values and properties are the result of extensive development work and practical experience. Our recommendations for application, whether given verbally or in writing, are intended to provide assistance in the selection of our products and do not establish a contractual relationship. In particular, they do not release those purchasing and applying our products from the duty of establishing for themselves, with due care, the suitability of our products for the intended application. Standard building industry practices must be complied with. We retain the right to make modifications to improve the products or their application. This edition supersedes all earlier editions.

